

MANGUERA INCENDIO PVC MODELO COMBAT F68 14 BAR

Color	RED								
Inner Lining	100% PVC								
Hose Jacket	High Tenacity Circular Woven Synthetic Yarn								
Outside Cover	100% PVC								
Temperature	-25°C - +80°C								
Length(M)	15,20,25.30. 60								
Elongation Rate:	<5%								
Expansion Rate:	<5%								
Abrasion Resistance:	>1500cycles								
Adhesion Strength:	>25N/25MM								
Nominal Size		Working Pressure		Min. Burst Pressure		Weight		Wall Thickness	
inch	mm	psi	bar	psi	bar	lbs/ft	kg/m	inch	mm
1 - 1/2"	38	250,300	17,21	750,900	51,63	0.235	0.35	0.083	2.1
1 - 3/4"	45	250,300	17,21	750,900	51,63	0.276	0.41	0.087	2.2
2"	52	250,300	17,21	750,900	51,63	0.316	0.47	0.087	2.2
2 - 1/2"	65	250,300	17,21	750,900	51,63	0.423	0.63	0.091	2.3

Package Details:

SIZE	PC/CARTON	CARTON SIZE	N.W(KG/PC)	G.W(KG/CTN)
1.5"×25M	1	51 × 48 × 9 cms.	9.8	10.3
2"×25M	1	51 × 48 × 11 cms.	12.5	13.5
2.5"×25M	1	54 × 51 × 13 cms.	15.9	16.9
2.5"×30M	1	55 × 55 × 13 cms.	20.4	21.4

Aplicación: Brigadas de Incendio, deshidratación, descarga de agua, drenaje, instalaciones de riego, bombeo de lodos y fertilizantes líquidos, aire comprimido, industria química, minas, etc.

Las mangueras son populares debido a su resistencia a la abrasión y al uso intensivo.

