

MANGUERA PVC/NITRILE MODELO COMBAT F68 21 BAR

Color	Rojo									
Inner Lining	70% Nitrile and 30% PVC									
Hose Jacket	High Tenacity Circular Woven Synthetic Yarn									
Outside Cover	70% Nitrile and 30% PVC, Ribbed Cover									
Temperature	-25°C+80°C									
Length(M)	25 Y 30									
Elongation Rate:	<5%									
Expansion Rate:	<5%									
Abrasion Resistance:	>2000 cycles									
Adhesion Strength:	>30N/25MM									
Nominal Size	Working Pressure		Min. Burst Pressure		Weight		Wall Thickness			
	inch	mm	psi	bar	psi	bar	lbs/ft	kg/m	inch	mm
1 - 1/2"	38	300	21	900	63	0.235	0.35	0.083	2.1	
1 - 3/4"	45	300	21	900	63	0.276	0.41	0.087	2.2	
2"	52	300	21	900	63	0.316	0.47	0.087	2.2	
2 - 1/2"	65	300	21	900	63	0.423	0.63	0.091	2.3	

Package Details:

SIZE	PC/CARTON	CARTON SIZE	N.W(KG/PC)	G.W(KG/CTN)
1.5"×25M	1	51 × 48 × 9 cms.	10.8	11.8
2"×25M	1	51 × 48 × 11 cms.	13.6	14.6
2.5"×25M	1	54 × 51 × 13 cms.	17.1	18.1

Aplicaciones: Uso excepcional Brigadas de incendio, deshidratación, descarga de agua, drenaje, instalaciones de riego, bombeo de lodos y fertilizantes líquidos, aire comprimido, industria química, minas, etc. Las mangueras son populares debido a su resistencia a la abrasión y al uso intensivo.

